
QUICK REFERENCE GUIDE > CID834DTB4

# 83cm Series 9 4 Zone Induction Cooktop with Integrated Ventilation

Series 9 | Minimal



A true two-in-one appliance, this cooktop combines the precision of induction cooking with powerful extraction in one seamless, stylish cooktop.

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone
- With nine fan speeds plus boost, select the perfect extraction rate for your cooking

Minimal style, sleek black glass finish to suit any kitchen design

## **DIMENSIONS**

 Height
 218 mm

 Width
 830 mm

 Depth
 515 mm

## **FEATURES & BENEFITS**

#### **Seamless Integration**

Offering true design freedom, this cooktop can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

#### **Elegant Design**

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these cooktops seamlessly blend with other appliances for a cohesive, considered kitchen design.

#### Precise Control

Fisher & Paykel induction cooktops offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

#### Effective Extraction

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

#### Safety Of Induction

Induction cooktops only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it - so they are safer for everyone.

#### Ease Of Use

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the cooktop surface.

## **Superior Efficiency**

Less heat is wasted during induction cooking because only the cookware is heated, not the cooktop surface. This makes induction cooking more energy-efficient than electric or gas cooktops.

#### **SPECIFICATIONS**

#### Accessories (sold separately)

Recirculation kit	82236 KRCID834 (optional)
Replacement recirculation filter	50182 FRO-DD (optional)
Square grille & butterfly valve for wall exhaust	82393 DO-G-SS (optional)

### Cleaning

Dishwasher safe grease filter

QUICK REFERENCE GUIDE > CID834DTB4

Flat easy clean glass surface	•	Elbow 90° vertical 222x89	82391 E90- V-222-89	Zone ratings		
Flush grille	•		V-222-03	Left front	2100W	
				Left front zone (PowerBoost set)	3000W	
Combinate		Performance		Left rear	2100W	
Controls		Gentle heat		Left rear zone (PowerBoost set)	3000W	
Auto cut-off timer for each zone	•	Heat settings	9	Right front	2100W	
Minute timer	•	-		Right front zone (PowerBoost set)	3000W	
Soft-touch electronic controls	•	Induction cooking technology	•	Right rear	2100W	
Touch and slide controls	•	Pause function	•	Right rear zone (PowerBoost set)	3000W	
		PowerBoost SmartZone	•	SmartZone	3700 W	
Downdraft performance						
Air outlet size	220mm W x 90 mm H	Power requirements		Zones		
Air speeds	9 + boost	Electrical connection	Terminal block	Number of zones	4	
Brushless motor	•	Maximum power	7.4 kW			
Ducted externally	•	Supply frequency	50 Hz			
Ducting Direction	Side, Rear	Supply voltage	220 - 240 V	SKU	82228	
Maximum air flow (Boost)	660 m³/hr					
Maximum air flow (Level 9)	623 m³/hr					
Maximum noise level (Boost)	70 dBA	Product dimensions		The product dimensions and specifications in this page product and model. Under our policy of continuous imp		
Maximum noise level (Level 9)	69 dBA	Depth	515 mm	dimensions and specifications may change at any time.		
Minimum air flow	192 m³/hr	Height	218 mm	check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel		
Minimum noise level	38 dBA	Width	830 mm	Appliances Ltd 2020	ner & Payker	
Ducting Accessories (optional)		Safety		Other product downloads available at fisherpa	ykel.com	
Duct 1m Connector 222x89	82389 D1-	Keylock	•			
	C-222-89	Pan detection system	•	→ 2D DWG Induction Cooktop with Integrate	ed Ventilation	
Ducting adaptor	82392 DA-219-98-150	Safety time out	•	<ul><li>2D DXF Induction Cooktop with Integrate</li><li>→ Archicad-23</li></ul>	d Ventilation	
Elbow 90° horizontal 222x89	82390 E90- H-222-89	Surface hot indicators	•	<ul> <li>✓ Installation Guide</li> <li>✓ Planning Guide</li> </ul>		

QUICK REFERENCE GUIDE > CID834DTB4



Revit



Rhino-5



Sketchup-8 User Guide

#### Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com