

76cm Series 9 Professional Warming Drawer

Series 9 | Professional



Keep plates warm until ready to serve, Rapid Proof or Slow Cook. Pair with a Professional style oven for design cohesion.

- A companion product, designed to match other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with an accessory rack for optimising space
- Easy to clean smooth glass base
- Six versatile tailored programs for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	271 mm
Width	761 mm
Depth	568 mm

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes in brushed stainless steel, for seamless pairing with our matching Professional style ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Soft-close with capacitive touch controls, this Warming Drawer comes with an accessory rack for optimising space.

Precise Control

With fast and even heating, this Warming Drawer is great for quickly proofing dough, low temperature cooking, resting meats or keeping dishes warm.

Safe And Sound

With automatic switch-off and Delayed Start functionality, our Warming Drawers help keep dishes warm until it is time to serve.

SPECIFICATIONS

Accessories (included)

Wire shelf	1
------------	---

Capacity

Accessory rack maximum allowable weight	42lbs
Cappuccino cups	24
Espresso cups	54
Place settings	16

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
Automatic timers	30', 45', 1h, 2h, 4h, 6h
Delayed start	•
Electronic capacitive touch controls	•
LED lights	1
On/Off indicator	•
Pre-set heating functions	•
Standby mode	•

Functions

Cups	•
Dehydrate	•
Plates	•
Rapid proof	•
Slow cook	•

Warm	•
<hr/>	
Performance	
Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
<hr/>	
Power requirements	
Amperage	10 A
Power cord length	1800 mm
Power outlet	Flex cord
Supply frequency	60 Hz
Supply voltage	240 V
<hr/>	
Product dimensions	
Adjustable front door panel to align with surrounding cabinetry	•
Depth	568 mm
Height	271 mm
Width	761 mm
<hr/>	
Safety	
Automatic turn off after 12 hours	•
Full extension slides	•
<hr/>	
SKU	82726
<hr/>	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) 2D-DWG Warming Drawer
- [↓](#) 2D-DXF Warming Drawer
- [↓](#) ArchiCAD Warming Drawer
- [↓](#) Installation Guide
- [↓](#) Planning Guide - 76cm Built-in Ovens and Companions - Professional
- [↓](#) Revit Warming Drawer
- [↓](#) SketchUp Warming Drawer
- [↓](#) User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 0800 372 273 W www.fisherpaykel.com