QUICK REFERENCE GUIDE > HC90PCB1

# 90cm Series 7 Pyramid Chimney Wall Rangehood

Series 7 | Classic



Pairing well with the black Classic Freestanding Cooker, this wall chimney rangehood extracts steam and cooking odours effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- · Dishwasher-safe filters that are easy to remove and clean
- Powerful 780m3/hr maximum airflow with edge-to-edge extraction
- · Energy-efficient LED lighting to illuminate your cooktop

## **DIMENSIONS**

Height	636-975 mr
Width	898 mr
Depth	500 mr

#### **FEATURES & BENEFITS**

## **Complementary Design**

This wall chimney rangehood is designed to match the black Classic Freestanding Cooker in both colour and style, including stylish chrome touch buttons.

#### Cleaner Air

Odours can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 780m3/hr, this rangehood removes cooking odours effectively, as well as grease and steam while cooking.

### **Intuitive Controls**

Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

#### Simple To Clean

Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

## **Design Quality**

Made from quality stainless steel with an excellent finish and robust product design, this rangehood is both visually appealing and durable.

#### Considered Efficiency

The extraction rate ensures interior air and climate is not excessively removed to the outside, while LED lighting on the rangehood has been chosen for energy efficiency.

#### Easy Installation

This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Freestanding Cooker. It can be either externally ducted or internally recirculated, for simple installation

## **SPECIFICATIONS**

## Accessories (included)

Aluminium filter	79256

## Accessories (sold separately)

Chimney extension	791774 (stainless steel), 793223 (black), 793224 (white), 793225 (red)
Eave ducting kit	PD-RHK 150E
Light bulb	792556
Recirculation carbon filter	792481
Recirculation diverter	792560
Roof ducting kit	PD-RHK 150T
Side wall ducting kit	PD-RHK 150W

## Fan ratings

Maximum air movement	780 m³/hr
Speed 3 sound rating	65 dBA

## Installation and cleaning

Air outlet size	150 mm
Dishwasher safe filters	7

QUICK REFERENCE GUIDE > HC90PCB1 Date: 07.09.2025 > 2

Ducted	vertical only
Recirculation	Optional
Stainless steel filter cover	•
Two piece height adjustable flue	•

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

## Performance

Surface
3
Mesh
3

#### Power requirements

Lighting power	8 W
Supply frequency	50 Hz
Supply voltage	230 V

#### **Product dimensions**

Depth	500 mm
Height	636-975 mm
Width	898 mm

#### Ventilation features

Light type	LED

SKU		50153

#### Other product downloads available at fisherpaykel.com

Archicad



Installation Guide



Revit Rhino



SketchUp



User Guide

## Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

