QUICK REFERENCE GUIDE > RS6019F2L1

60cm Series 9 Integrated Dual Zone Freezer

Series 9 | Integrated



Pair with the Integrated Dual Zone Refrigerator for the ultimate kitchen solution - this model features two independent food zones taking cooling flexibility to a new level.*


- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory
- Flush fit design with 4mm gaps and custom height installation
- Two independent food zones with adjustable temperature from -21 to -14°C
- · Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm

Width 592 mm

Depth 576 mm



FEATURES & BENEFITS

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Independent Food Zones

When it comes to optimal food preservation, one temperature does not fit all. With two independent food zones, you can create the perfect climate for storing different foods. Each zone has adjustable temperature from -21°C to -14°C, ideal for items such as meat, seafood, frozen desserts and ice.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your freezer and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Flexible Storage

Designed to make it simple for you to store, access and remove food, this freezer includes LED-lit adjustable cantilevered shelving and full extension bins.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the freezer door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories (included)	
Hinge change (from left hinge to right hinge)	•
Joiner kit	AJRS19LR
Accessories (sold separately)	
Door panel set stainless steel	Right & Left hinge RD6019
Handle kit Classic	AHCLRDSF
Handle kit Contemporary round, aluminium	AHSRDSF
Handle kit Contemporary square fine, aluminium	AHD5RDSF
Handle kit Contemporary square fine, black	AHD5RDSFB
Handle kit Professional round flush	AHP3RDSF
Toe kick stainless steel 1200mm	AKRS12010
Toe kick stainless steel 1800mm	AKRS18010
Toe kick stainless steel 600mm	AKRS06010
Capacity	
Total gross capacity	329 L
Volume	304 L
Volume freezer	304 L
Consumption	
Energy rating	4 star
Energy usage	256kWh/year
In-use energy carbon emissions estimate	24.3kgCO2e/year

Adjustable glass cantilevered shelves	
Adjustable glass shelves	2
Smart appliance	
SmartTouch control panel	•
Freezer Features	
Bottle chill	•
Door alarm	•
Fast freeze	•
Freezer bins	2
LED ceiling lighting	
LED ceiling lighting Installation Dimensions Minimum inside width of cabinetry frame	600 mm
Installation Dimensions	600 mm
Installation Dimensions Minimum inside width of cabinetry frame	600 mm
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry	600 mm
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry Minimum internal height of cabinetry	600 mm
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry Minimum internal height of cabinetry Performance	600 mm
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare	
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare Adaptive defrost	600 mm
Installation Dimensions Minimum inside width of cabinetry frame Minimum internal depth of cabinetry Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare Adaptive defrost Dual evaporator	600 mm

Adjustable glass shelves	2
Smart appliance	•
SmartTouch control panel	•
Freezer Features	
Bottle chill	
Door alarm	•
Fast freeze	•
Freezer bins	2
LED ceiling lighting	•
Minimum inside width of cabinetry frame	600 mm
Minimum internal depth of cabinetry Minimum internal height of cabinetry	
Minimum internal height of cabinetry	
Minimum internal height of cabinetry	
Minimum internal height of cabinetry Performance	
Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare	600 mm
Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare Adaptive defrost	
Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare Adaptive defrost Dual evaporator	
Minimum internal height of cabinetry Performance ActiveSmart™ Foodcare Adaptive defrost Dual evaporator Frost free	

Rated current	10 A
Supply frequency	50 Hz
Supply voltage	230 V

Product	dimensions
FIUUUCL	ullilelisiolis

Depth	576 mm
Height	1870 mm
Width	592 mm

SKU	26198
SKU	26198

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

DWG K08 Hinge DWG DWG Appliance with Custom Panel

DXF K08 Hinge


DXF Appliance with Custom Panel DXF with Panel Preparation

Archicad

Energy Rating

Installation Guide - Assisted Opening Accessory - Integrated Refrigeration (English)

QUICK REFERENCE GUIDE > RS6019F2L1 Date: 21.10.2025 > 3



↓ Planning Guide (English)

↓ Revit

↓ Rhino

Rhino

L Rhino

↓ Rhino

↓ Rhino

Rhino

↓ SketchUp

↓ SketchUp Appliance with Custom Panel

, SketchUp Appliance Door with Contemporary Round Handle

SketchUp Appliance Door with Professional Round Flush
Handle

SketchUp Appliance Door with Square Fine Black Handle

SketchUp Appliance Door with Square Fine Handle

User Guide Integrated Refrigerator & Freezer

 $\underline{\downarrow}$

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

